

# Polyethylene DPM



## Overview

A damp proof membrane (DPM) or vapour control layer (VCL) is a material used in to protect the floor and the insulation from moisture.

The DPM is usually installed on the concrete slab, prior to the insulation layer being installed, thus creating a moisture barrier that prevents rising damp.

After installing the insulation layer, a VCL is installed on top before the screed layer is poured to prevent the insulation absorbing moisture from the screed.

Warmup provides two types, a 1200 gauge DPM and 500 gauge VCL. The DPM can be used in place of the VCL but not vice versa.

## Technical specifications

Product code	WHS-X-POL500	WHS-X-POL1200
Gauge	500 gauge / 0.125mm	1200 gauge / 0.300mm
Dimensions	4m x 25m	
Area	100m <sup>2</sup>	
Material	Polyethylene	
Colour	Black	

## Contact

### Warmup plc

www.warmup.co.uk T: 0345 345 2288  
uk@warmup.com F: 0345 345 2299

Warmup plc ■ 704 Tudor Estate ■ Abbey Road ■ London ■ NW10 7UW ■ UK

Warmup GmbH ■ Ottostraße 3 ■ 27793 Wildeshausen ■ DE

Warmup - TS - DPM - V1.0 - 2023-05-11\_EN

**Warmup**<sup>®</sup>